



MC 5054

UNIVERSAL HIGH QUALITY MICROPHONE



Description

MC 5054 is a condenser microphone with high quality capsule, mounted on a flexible arm 445 mm long, and to be installed on microphone support with XLR connector. It is powered with phantom from 9 V to 52 V and windshield polyurethane foam. It has a LED ring on microphone-head and the MAX SPL the capsule can withstand is140 dB.

- Features
- › Electret condenser microphone

› Unidirectional, cardioid polar diagram

› Frequency response 50 Hz - 18.000 Hz

› Max input SPL 140 dB

› Output impedance 200 Ohm

› Phantom power 9V ~ 52V DC

› LED ring on microphone-head

› Windscreen included

Part Number

14115024 MC 5054

Black



EAN 8024530012007



MC 5054

UNIVERSAL HIGH QUALITY MICROPHONE

Line Art 2D



Microphone specifications

TECHNICAL SPECIFICATIONS

Type	Electret
Directivity	Cardioid
Sensitivity	-65 dB
Frequency Response (-3dB)	50 Hz - 18 kHz
Output impedance (ohm)	200.00 ohm
Phantom power	Yes
Phantom Power	9 V DC - 52 V DC

Standard compliance

Safety agency	CE compliant
---------------	--------------

Physical specifications

Cabinet/Case Material	Metal
Color	Black

Size / Weight

Height	540 mm / 21.26 inches
Diameter	21 mm / 0.83 inches