



GIUNO 300

Product Code: SG GIUNO300

Moving head spot CMY zoom



Light source

- 1x270W White led
- Color temperature: 7500K
- LED lifespan: >50.000h
- Led refresh frequency: >400Hz anti-flicker

Optic system

- Beam angle: motorized zoom from 3° to 50°
- Electronic focus
- Luminous flux: 21000 LUX@5m (3° Min Zoom), 1400 LUX@5m (50°Max Zoom)

Color system

- CMY color mixing + CTO
- Color wheel: 7 dichroics filters + white

Effects

- Static gobo wheel: 5 static gobos + 1 animation effect
- Rotating gobo wheel: 7 rotating gobos, bidirectional rotation, indexable interchangeable with plug & play system - Gobo size 25mm / focus 19mm
- Gobo scroll effect with adjustable speed
- 3 facets rotating circular prism with adjustable speed
- 5 facets rotating linear prism with adjustable speed
- Color rainbow effect in both directions
- Iris
- Frost filter
- High precision and fast zoom
- Linear dimmer 0-100%, high resolution
- High speed electronic strobe with adjustable speed, max 25 flashes/s
- Random strobe and pulse effect with adjustable speed

Control and programming

- 2 different dmx configurations available: 23/28 channels
- Protocol USITT DMX512, Art-Net
- Wireless Solution dmx receiver board included
- Pan&Tilt 8/16 bit selectable resolution
- Master/Slave mode
- DMX recorder and scene editor from display
- Reset via dmx

Structure and cabinet

- Black metal housing and plastic covers with high resistance
- LCD color graphic display
- Pan&tilt three-phases motors
- Pan 540° , Tilt 270°
- Automatic Pan&Tilt repositioning after accidental movement
- Pan&Tilt quick-lock system
- Mounting points: 1 pair of ¼ turn lock omega holders

- 3 poles XLR in/out dmx signal connections
- RJ45 ethercon in/out signal connection (Art-NET)
- Forced air cooling system with electronic control

Power supply

- Input Voltage: AC~100-240V 50/60Hz
- Switching power supply unit
- Max power: 420W @ 230VAC
- Power in connection through Powercon connector
- Power supply cable included

Weight and dimesions

- Net weight: 29 kg
- Dimensions:410x290x690 mm

Technical specifications and appearances are subject to change without notice and accuracy is not guaranteed. All trademarks are the property of their respective owners. PROEL accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colors and specifications may vary from actual product. PROEL products are sold through authorized fullfillers and resellers only. This manual is copyrighter. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of PROEL - Via alla Ruenia 37/43 - CAP 64027 - Sant'Omero (TE) ITALY.

Sagitter is a brand of Proel Spa | Via alla Ruenia
37/43 64027 Sant'Omero (TE) ITALY
Tel. +39 0861 81241 | Fax. +39 0861 887862 |
www.sagitter.com

