

LF15G401

WOOOFER

DESCRIPTION

The LF15g401 is a 15-inch woofer with linear frequency response cheracteristics and very high power handling.

The LF15G401 uses a fibre loaded cone assembly along with a high excursion triple roll, constant geometry surround. This combination provides remarkable strength and a peak to peak maximum excursion of 52mm.



FEATURES

- 4-inch, fiberglass inside/outside copper voice coil
- 1600W continuous program power handling
- 97 dB Sensitivity
- 30 Hz 1.5 kHz Frequency range
- Dual spider design with silicon based dampening control
- Triple-roll surround and corrugated straight cone geometry



TECHNICAL SPECIFICATIONS

| General specifications | Nominal Diameter: | 15 inch / 381 mm |
|------------------------|-------------------|------------------|
|------------------------|-------------------|------------------|

Rated Impedance: 8 ohm
Program Power (watt): 1600 W
Power handling capacity: 800 W
Sensitivity: 97 dB
Frequency range: 35 - 1500 Hz

Effective piston diameter: 340 mm / 13.39 inch
Max. Excursion Before Damage: 52 mm / 2.05 inch

Minimum Impedance (ohm): 6 ohm

Voice Coil Diameter: 4.0 inch / 102 mm

Voice Coil Winding Material: Copper

Voice Coil Length: 23 mm / 0.91 inch

Number of layers: 2

Kind of layers: inside/outside

Top Plate Thickness: 12 mm / 0.47 inch

Cone Design: Straight
Surround Material: Polycotton
Surround Design: Triple roll
Magnets: Ceramic

Spider: Dual with silicon based damping control

4.80 ohm

2.50%

Thiele - small parameters Resonance frequency (Fs): 36 Hz

DC resistance (Re) (ohm):

Mechanical factor: 6.20 Qms 0.27 Qes Electrical factor: Total factor: 0.26 Qts BI factor (BI) (T x m): 24.60 T x m Effective moving mass (Mms): 150 gr Equivalent Cas air loaded (Vas): 150 liters Effettive piston area (Sd): 0.09 m2 Max. linear excursion (Xmax): 9 mm Voice coil inductance @ 1kHz (Le1k): 1.80 mH

Mounting informations Overall diameter: 393 mm / 15.47 inches

Half-space efficency (Eff):

Bolt circle diameter: 371-376 mm / 14.61-14.8 inch

Bolt hole diameter: 7 mm / 0.28 inch
Front mount baffle cut-out: 352 mm / 13.86 inch
Rear mount baffle cut-out: 360 mm / 14.17 inch
Volume occupied by the driver: 4.3 liters / 0.17 ft3

Standard compliance CE marking: Yes

DATASHEET



 Size
 Height:
 154 mm / 6.06 inches

 Diameter:
 393 mm / 15.47 inches

Weight: 13 kg / 28.66 lbs

Shipping informations Package Height: 220 mm / 8.66 inches

Package Width: 440 mm / 17.32 inches
Package Depth: 440 mm / 17.32 inches
Package Weight: 14 kg / 30.86 lbs

PART NUMBER

• 11100014

LF15G401 8ohm







