

MB8N251

MID - BASS

DESCRIPTION

The MB8N251 is a 8" neodymium mid-bass driver with an excellent linearity, good efficiency and high power handling capabilities. The 2,5" aluminium voice coil combined with a high strength fibreglass former allows high efficiency and good frequency response extension. Aluminium basket and magnetic assembly design provide an excellent heat dissipation and very low power compression. The M-roll surround shape combined to spider design offer good linear displacement and precise low frequency reproduction.



FEATURES

- 2.5-inch , fibreglass former, aluminum voice coil
- 600 Watt continuous program power handling
- 96 dB Sensitivity
- 60 Hz - 3.5kHz Frequency range
- Forced air ventilation
- M-roll surround and exponential cone geometry

TECHNICAL SPECIFICATIONS

General specifications

Nominal Diameter:	8 inch / 203 mm
Rated Impedance:	8 ohm
Program Power (watt):	600 W
Power handling capacity:	300 W
Sensitivity:	96 dB
Frequency range:	60 - 3500 Hz
Effective piston diameter:	165 mm / 6.5 inch
Max. Excursion Before Damage:	40 mm / 1.57 inch
Minimum Impedance (ohm):	6 ohm
Voice Coil Diameter:	2.5 inch / 63 mm
Voice Coil Winding Material:	Aluminium
Voice Coil Length:	14 mm / 0.55 inch
Number of layers:	1
Kind of layers:	outside
Top Plate Thickness:	9 mm / 0.35 inch
Cone Design:	Curved
Surround Material:	Polycotton
Surround Design:	M-roll
Magnets:	Neodymium
Dual-force air ventilation:	Yes
Spider:	Single

Thiele - small parameters

Resonance frequency (Fs):	68 Hz
DC resistance (Re) (ohm):	5.10 ohm
Mechanical factor:	4.60 Qms
Electrical factor:	0.26 Qes
Total factor:	0.25 Qts
Bl factor (Bl) (T x m):	15.20 T x m
Effective moving mass (Mms):	27 gr
Equivalent Cas air loaded (Vas):	13 liters
Effective piston area (Sd):	27.20 m ²
Max. linear excursion (Xmax):	5 mm
Voice coil inductance @ 1kHz (Le1k):	1.30 mH
Half-space efficiency (Eff):	1.70%

Mounting informations

Overall diameter:	239 mm / 9.41 inches
Bolt circle diameter:	221-227 mm / 8.7-8.94 inch
Bolt hole diameter:	7 mm / 0.28 inch
Front mount baffle cut-out:	185 mm / 7.28 inch
Rear mount baffle cut-out:	185 mm / 7.28 inch
Volume occupied by the driver:	0.6 liters / 0.02 ft ³

Standard compliance

CE marking:	Yes
-------------	-----

Size

Height:	102 mm / 4.02 inches
Diameter:	208 mm / 8.19 inches
Weight:	2.01 kg / 4.43 lbs

Shipping informations

Package Height:	125 mm / 4.92 inches
Package Width:	235 mm / 9.25 inches
Package Depth:	220 mm / 8.66 inches
Package Weight:	2.47 kg / 5.45 lbs

PART NUMBER

- **11100061**

MB8N251

8ohm



