

HPC210RD

Professional balanced microphone cable (2 x 0,22 mm²) with flexible overall jacket - O.F.C. (Oxygen Free Copper). Red color.



Description

Professional balanced microphone cable (2 x 0,22 mm²) with flexible overall jacket - O.F.C. (Oxygen Free Copper). Available colors: Black, Blue, Bronze, Green, Purple, Red, White, Yellow.

Technical Specifications HPC210RD

Application fields: Recording studios / Microphone connections

Conductors: Bare copper 24 AWG = 30 x 0.10 mm (0.22 mm²)

Insulation: Super flexible PVC HT105 Ø 1.60 mm

Shield: Spiral copper 16x5x0.10 mm > 90%

Jacket: Flexible PVC 60 shore Ø 6.50 mm

Color: Red

Electrical resistance:

93 Ohm/Km (conductor) @ 20°C

20 Ohm/Km (shield) @ 20°C

Electrical capacitance:

46 pF/m (conductor/conductor) @ 1 KHz

90 pF/m (conductor/shield) @ 1 KHz

Velocity of propagation: 80 %

Operating temperature: -20°C / +70°C

Working tension:

Weight: 46 Kg/Km

Minimum bending radius: 20 x cable section radius

Packaging:

100 m carton reel