

EVE P-100 WW

Warm, bright and even wash is at hand with EVE P-100 WW, a high output warm white (3500 K) wash light designed for mobile and installation applications. It includes interchangeable magnetic lenses to alter the beam to desired angles. EVE P-100 WW features a built-in gel frame holder and handy 6¼-inch accessory slot to hold barn doors. Its fanless design ensures 100% silent operation making it great for quiet applications. High-frequency LED dimming eliminates flicker making EVE P-100WW great for video and broadcast applications. D-Fi USB compatibility is on board for wireless master/slave or DMX control as well as powerCON®-compatible power input/output connections for power linking. Sturdy cast aluminum housing provides extra strength without the weight. EVE P-100WW fits best in the CHS-40 VIP gear bag.



HIGHLIGHTS

- High output warm white (3500 K) wash light designed for mobile and installation applications
- Included interchangeable magnetic lenses alter the beam to desired angles
- Built-in gel frame holder and 6¼-inch accessory slot to hold barn doors
- Fanless design ensures 100% silent operation
- Flicker-free on video due to the high-frequency LED dimming
- D-Fi USB compatibility for wireless master/slave or DMX control
- Cast aluminum housing provides extra strength without the weight
- powerCON®-compatible power input/output connections for power linking
- Fits best in the [CHS-40](#) VIP gear bag

SPECIFICATIONS

- DMX Channels : 1, 2 or 4
- DMX Connectors : 3- and 5-pin XLR
- Light Source : 1 COB (warm white) 100 W, (2.7 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 25 Hz
- Beam Angle : 35°, 65°, or 67°
- Field Angle : 58°, 96°, or 89°
- Illuminance : (35°): 6,085 lux @ 2 m (lens 1)
(67°): 2,532 lux (no lens) @ 2 m
(65°): 2,050 lux @ 2 m (lens 2)
(35°): 974 lux @ 5 m (lens 1)
(67°): 405 lux @ 5 m (no lens)
(65°): 328 lux @ 5 m (lens 2)
- Lumens : 11,322
- Power Linking : 7 units @ 120 V; 14 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 122 W, 1.2 A 120 V, 60 Hz
119 W, 0.5 A @ 230 V, 50 Hz
- Weight : 7.6 lb (3.5 kg)
- Size : 8.6 x 9.65 x 12 in (220 x 245 x 305 mm)
- Approvals : CE, MET
- Accessory Holder/Gel Frame Size : 6.25 in (158.75 mm)
- Color Temperature : 3500 K
- Optional Controllers : [D-Fi USB](#)
- CRI : 98

WHAT'S INCLUDED

- EVE P-100 WW
- Lens 1 and Lens 2
- Power cord
- PowerCON to bare end (EU only)
- Gel Frame
- Hanging bracket
- Quick Reference Guide